

CD850 2.0

DRIVER

DESCRIPTION

The CD850 2.0 is a high performance 3.0-inch diaphragm compression driver with a 2 inch exit throat featuring several state of the art technologies.

The diaphragm are precision formed from pure titanium. The suspension is based on a vented and damped design in order to provide low distorsion. Voice coil assembly is designed using high temperature kapton former.



FEATURES

- 3-inch Diaphragm, 2-inch Exit Throat / Pure Titanium Compression Driver
- 220W continuous program power handling
- Frequency range: 500Hz 20kHz
- 3-slot optimized geometry phase plug
- Ceramic Magnet Assembly
- Copper inductance ring for extended response
- Vented, damped, low distortion suspension system



TECHNICAL SPECIFICATIONS

General specifications	Exit Throat Diameter:	2.0 inch / 51 mm
------------------------	-----------------------	------------------

Related Impedance: 8 ohm
Program Power (watt): 220 W
Power handling capacity (watt): 110 W
Sensitivity: 109 dB

Frequency range: 500 - 20000 Hz
Diaphragm Material: Pure Titanium
Suspension Material: Polyester
Suspension Design: Flat
Minimum Impedance (ohm): 8.50 ohm

Voice Coil Diameter:3.0 inch / 76 mmVoice Coil Material:Edgewound AluminiumVoice Coil Former Design:Straight - Kapton

Number of layers:

Kind of layers:outsideFlux Density:1 TPhase Plug Design:3 slot

Phase Plug Material:

Magnetics:

Voice Coil Demodulation Ring

PP Composite

Ceramic

Copper

Thiele - small parametersBl factor (Bl) (T x m): 12.30 T x m

Mounting informationsOverall diameter: 180 mm / 7.09 inches

Overall height: 88 mm / 3.46 inches

Mounting: 4 x 6 mm threaded holes at 90°

Standard compliance CE marking: Yes

Size Weight: 5.72 kg / 12.61 lbs

Shipping informations Package Height: 119 mm / 4.69 inches

Package Width: 214 mm / 8.43 inches
Package Depth: 214 mm / 8.43 inches
Package Weight: 5.97 kg / 13.16 lbs

PART NUMBER

· 15129044

CD850 2.0 8ohm

