









1/4" BALANCED LINE OUTPUTS

NEUTRIK™ COMBO JACK INPUT

48V PHANTOM POWER

HIGH-POWER HEADPHONE AMPLIFIER




The Al-1 is a studio-grade audio interface suitable for connecting both microphones and musical instruments to a computer or tablet.

It features an ultra-low-noise preamp, a high-power headphone amplifier, and balanced line outputs. Switchable 48V phantom power facilitates the connection of condenser microphones, and zero-latency monitoring mode allows for seamless recording.

- • Single channel audio interface
- • 2 x 1/4" balanced line outputs
- Neutrik™ combo jack input
- • 48V phantom power

Front view



50mm



ACOUSTIC & ELECTRICAL SPECIFICATIONS	
Computer Connectivity:	USB
Form Factor:	Desktop
Simultaneous I/O:	1 x 2
Number of Preamps:	1
Phantom Power:	Yes
Bit Depth:	24-bit
Sample Rates:	44.1 kHz 48 kHz 88.2 kHz 96kHz
Analog Inputs:	1 x Neutrik XLR-1/4" combo
Analog Outputs:	2 x 1/4" (impedance balanced) 1 x 1/4" (headphones)
Direct Monitor:	Yes
USB:	1 x USB Type C
Bus Powered	Yes
OS Requirements	Mac OS 10.10 or later Windows 7 or later
Power:	USB bus-powered
MECHANICAL SPECIFICATIONS	
Net Weight (Grams):	560
Heigh x Width x Depth (millimetres):	38 x 124 x 100 total (with knobs, 88 without knobs)

