



Die platzsparende Konsole verfügt über zwei Bereiche mit jeweils acht Fadern. Sie kann allein, aber auch kaskadiert zusammen mit einer anderen CL-Konsole verwendet werden.

- Input channels: 48 mono, 8 stereo.
- Fader configuration: 8-fader left section, 8-fader Centralogic section, 2-fader master section .
- Meter bridge optional.

Technische Daten

General specifications		
Sampling frequency rate	Internal	44.1kHz / 48kHz
	External	44.1kHz: +4.1667%, +0.1%, -0.1%, -4.0% (± 200 ppm), 48kHz: +4.1667%, +0.1%, -0.1%, -4.0% (± 200 ppm)
Signal delay		Less than 2.5ms, OMNI IN to OMNI OUT, Fs=48kHz
Total harmonic distortion		Less than 0.05% 20Hz-20kHz@+4dBu into 600 Ω , OMNI IN to OMNI OUT, Input Gain = Min.
Hum & noise level	Equivalent input noise	-128dBu typ., Equivalent Input Noise, Input Gain=Max
	Residual output noise	-88dBu, Residual output noise, ST master off
Crosstalk		-100dB*1, adjacent OMNI IN/OMNI OUT channels, Input Gain = Min.
Power requirements		US/Canada: 120V 60Hz, Japan: 100V 50/60Hz, China: 110-240V 50/60Hz, Korea: 220V 60Hz, Other: 110-240V 50/60Hz
Dimensions	W	648mm (25 5/8in)
	H	299mm (11 3/4in)
	D	667mm (26 1/4in)
Net weight		24kg (52.9lb)
Frequency response		+0.5, -1.5dB 20Hz-20kHz, refer to +4dBu output @1kHz, OMNI IN to OMNI OUT
Power consumption		170W: Internal Power Supply / 200W: Simultaneous use of Internal PSU and External PW800W
Others		Temperature Range: Operating temperature range: 0 - 40 \square , Storage temperature range: -20 - 60 \square
Dynamic range		112dB typ.: DA Converter / 108dB typ.: OMNI IN to OMNI OUT, Input Gain = Min.